

CS501

5.25" 2-Way, In-Ceiling, Coaxial, Infinite Baffle Loudspeaker

The easy to install CS501 is a full-range ceiling loudspeaker that incorporates an Injection Molded Graphite woofer with a butyl rubber surround and Ferrofluid cooled titanium coated polycarbonate tweeter. The tweeter allows for deeper penetration into the room and concentrated sound to the sweet spot.

This revolutionary combination provides superior and more natural sound for both foreground and background applications. The Infinite Baffle design makes it the ideal choice for typical applications in open beam attic or enclosed ceilings.

The speaker color is white, and is a close match to Frazee White Shadow 181. It can be painted to match any décor. The speaker enclosure is a durable UV-resistant material that allows for both indoor and outdoor installations. The perforated powder-coated aluminum alloy grill is long-lasting, corrosion resistant and rust-free.

Four built-in expanding transverse dog leg clamps permit installation with or without pre-wire construction brackets in drywall or material with thickness of 7/32" to 1 3/16".

Electrical connection, up to 12-gauge wire, is made by gold plated constant tension spring-loaded terminals.

This speaker is also available in a quick connect small bezel edge FastLoc Grill.

Part Number	92021
Manual URL	www.currentaudio.com
Accessories	Volume Control ZL45R Part# 92034 SpeKap Part # 92069



SPECIFICATIONS

Driver	5.25" Injection Molded Graphite Cone with Butyl Rubber Surround
Tweeter	.75" (19mm) Titanium Coated Polycarbonate Ferrofluid Cooled Dome
Crossover	Gold press terminals
Grill specification	Perforated Aluminum with Scrim Cloth
Frequency Response	55Hz - 19kHz
Impedance (nominal)	8 ohms
Power Handling	5 - 45 Watts
SPL	89 dB 1W/1m
Diameter x Depth	8" (203mm) x 3 1/4" (83mm)
Retrofit Cutout Diameter	6 1/2" (165mm)
Standard Pair Pack Dimensions (weight)	11 1/4" x 9" x 9 1/2" (6 lbs)
Master Pack Dimensions 2 pair (weight)	18 1/2" x 12" x 10 1/4" (15 lbs)

