

CS804

8.0" 2-Way, In-Ceiling, Coaxial, Infinite Baffle Loudspeaker

The easy to install CS804 is a full-range ceiling loudspeaker that incorporates an ultra light Woven Carbon Fiber woofer with a butyl rubber surround and a diffractionless ceramic coated aluminum dome Ferrofluid cooled tweeter. This patent pending pivoting tweeter allows for deeper penetration into the room and a concentrated sound to the sweet spot.

This revolutionary combination provides superior and more natural sound for both foreground and background applications.

In addition the CS804 incorporates a 3 position equalization switch, one each for bass and treble to finetune the acoustics and allow for various room surfaces.

For efficiency and consistency the CS804 is timbre matched to the FIT804 and WS804 series of speakers.

The speaker color is white, and is a close match to Frazee White Shadow 18lit can be painted to match any decor. The speaker enclosure is a durable UV-resistant material that allows for both indoor and outdoor installations.

The perforated powder-coated aluminum alloy grill is long lasting, corrosion resistant and rust-free.

Four built-in expanding transverse dog leg clamps permit installation with or without pre-wire construction brackets in drywall or material with thickness of 5/16" to 1 3/16".

Electrical connection, up to 12-gauge wire, is made by four gold plated constant tension spring-loaded terminals.

This speaker is also available in a quick connect small bezel edge FastLoc Grill.

With our limited Lifetime warranty you are assured years of superior trouble-free operation.



SPECIFICATIONS

Driver	8" Woven Carbon Fiber Cone with Butyl Rubber Surround
Tweeter	Patent Pending Pivoting, Defraction-less 1" (25mm) Ceramic Coated Aluminum Ferrofluid Cooled Dome
Crossover	3 position EQ switches for Driver and Tweeter adjustments, gold press terminals
Grill specification	Perforated Aluminum with Scrim Cloth
Frequency Response	33Hz - 21kHz
Impedance (nominal)	8, 6 or 4 ohms dependent upon driver EQ switch setting
Power Handling	5 - 150 Watts
SPL	91.5 dB 1W/1m
Diameter x Depth	11 3/64" (281mm) x 4 3/8" (111mm)
Retrofit Cutout Diameter	9 3/4" (247mm)
Standard Pair Pack Dimensions (weight)	13 1/4" x 12 3/4" x 12 3/4" (15 lbs)
Master Pack Dimensions 2 pair (weight)	26" x 14" x 13 3/4" (31 lbs)

Part Number	92014
Manual URL	www.currentaudio.com
Accessories	<p>TB8 Tile Support Bridge Part# 92084</p> <p>R70VT Transformer, 8ohm, 70V, Part# 92070</p> <p>Volume Control ZL45R Part# 92034</p> <p>SpeKap Part # 92069</p>



CURRENTAUDIO®

©2012 Current Audio LLC • 1830 John Towers Avenue, El Cajon, CA 92020 • Sales 866-927-7181

All product specifications are subject to change without notice.

Rev. SS-CS804 02/12