

FIT654

6.5" 2-Way, In-Ceiling, Coaxial, Infinite Baffle Loudspeaker

The easy to install FIT654 is a full-range ceiling loudspeaker with Focused Image Technology™. It incorporates an ultra light Woven Carbon Fiber woofer with a butyl rubber surround and the diffraction-less ceramic coated aluminum dome pivoting Ferrofluid cooled tweeter. This Patent Pending pivoting tweeter allows for deeper penetration into the room and a concentrated sound to the sweet spot. This revolutionary combination provides superior and more natural sound for both foreground and background applications.

The FIT series speakers additionally incorporate the unique Patent Pending Three Dimensional Positioning (3-DP) woofer. This design allows the user to separately adjust the angle, tilt and rotation of the woofer so you can direct the sound where you want it, not where you install it.

The Positive Position Lock system (PPL) uses two screws on either side of the woofer that pull the back plane tight and locks the position in place.

In addition, the FIT654 contains a 3 position equalization switch, one each for bass and treble to fine-tune the acoustics and allow for various room surfaces. The Infinite Baffle design makes it the ideal choice for typical applications in open beam attic or enclosed ceilings.

For efficiency and consistency the FIT654 is timbre matched to the CS654 series of speakers.

The speaker color is white, and is a close match to Frazee White Shadow 181. It can be painted to match any décor. The speaker enclosure is a durable UV-resistant material that allows for both indoor and outdoor installations. The perforated powered coated aluminum alloy grill is long lasting, corrosion resistant and rust-free.

Four built-in expanding transverse dogleg clamps permit installation with or without pre-wire construction brackets in drywall or material with thickness of 5/16" to 1 5/16".

Electrical connection, up to 12 gauge wire, is made by gold plated constant tension spring-loaded terminals.

This speaker is also available in a quick connect small bezel edge FastLoc Grill.

With our limited 5 year warranty you are assured years of superior trouble free operation.

Part Number	92048
Manual URL	www.currentaudio.com
Accessories	Volume Control ZL45R Part# 92034 SpeKap Part # 92069



SPECIFICATIONS

Driver	6.5" Woven Carbon Fiber Cone with Butyl Rubber Surround
Tweeter	Patent Pending Pivoting, Diffraction-less 1" (25mm) Ceramic Coated Aluminum Ferrofluid Cooled Dome
Crossover	3 position EQ switches for Bass and Tweeter adjustments, gold press terminals
Grill specification	Perforated Aluminum with Scrim Cloth
Frequency Response	35Hz - 21 kHz
Impedance (nominal)	8, 6 or 4 ohms dependent upon driver EQ switch setting
Power Handling	5 - 150 Watts
SPL	91.5 dB 1W/1m
Diameter x Depth	9 7/8 (251mm) x 5 5/8" (143mm)
Retrofit Cutout Diameter	8 3/8" (213mm)
Standard Pair Pack Dimensions (weight)	11 1/2" x 15" x 12 1/2" (11 lbs)
Master Pack Dimensions 2 pair (weight)	37 3/4" x 13 1/2" x 13 1/2" (22 lbs)

