

CS650

6.5" 2-Way, In-Ceiling, Coaxial, Infinite Baffle Loudspeaker

The easy to install CS650 is a full-range ceiling loudspeaker that incorporates the MetaPlex woofer with a butyl rubber surround and diffraction-less silk dome Ferrofluid cooled tweeter. This patent pending pivoting tweeter allows for deeper penetration into the room and concentrated sound to the sweet spot. This revolutionary combination provides superior and more natural sound for both foreground and background applications. The Infinite Baffle design makes it the ideal choice for typical applications in open beam attic or enclosed ceilings.

For efficiency and consistency the CS650 is timbre matched to the FIT650, CS650DT, and WS650 series of speakers.

The speaker color is white, and is a close match to Frazee White Shadow 181. It can be painted to match any décor. The speaker enclosure is a durable UV-resistant material that allows for both indoor and outdoor installations. The perforated powder-coated aluminum alloy grill is long-lasting, corrosion resistant and rust-free.

Four built-in expanding transverse dog leg clamps permit installation with or without pre-wire construction brackets in drywall or material with thickness of 3/16" to 1 3/16".

Electrical connection, up to 12-gauge wire, is made by gold plated constant tension spring-loaded terminals.

This speaker is also available in a quick connect small bezel edge FastLoc Grill.

With our limited lifetime warranty you are assured years of superior trouble free operation.

Part Number	92020
Manual URL	www.currentaudio.com
Accessories	TB8 Tile Support Bridge Part# 92083 R70VT Transformer, 8ohm, 70V, Part# 92070 Volume Control ZL45R Part# 92034 SpeKap Part # 92069



SPECIFICATIONS

Driver	6.5" MetaPlex Composite Cone with Butyl Rubber Surround
Tweeter	Patent Pending Pivoting, Diffraction-less 1" (25mm) Silk Ferrofluid Cooled Dome
Crossover	Gold press terminals
Grill specification	Perforated Aluminum with Scrim Cloth
Frequency Response	42Hz - 20kHz
Impedance (nominal)	8 ohms
Power Handling	5 - 100 Watts
SPL	90 dB 1W/1m
Diameter x Depth	9 5/8" (284mm) x 3 3/4" (95mm)
Retrofit Cutout Diameter	8 5/32" (207mm)
Standard Pair Pack Dimensions (weight)	11" x 13" x 12" (10 lbs)
Master Pack Dimensions 2 pair (weight)	22" x 13" x 12" (20 lbs)

