

WS650

6.5" 2-Way, In-Wall, Full Range Loudspeaker

The easy to install WS650 is a full-range In-Wall loudspeaker that incorporates the famous MetaPlex woofer with a butyl rubber surround and a silk dome Ferrofluid cooled tweeter. This tweeter allows for deeper penetration into the room and concentrated sound to the sweet spot. This revolutionary combination provides superior and more natural sound for both foreground and background applications.

For efficiency and consistency the WS650 is timbre matched to the FIT650, CS650DT, and CS650 series of speakers.

The speaker color is white, and is a close match to Frazee White Shadow 181. It can be painted to match any décor. The speaker enclosure is a durable UV-resistant material that allows for both indoor and outdoor installations. The perforated powder-coated aluminum alloy grill is long lasting, corrosion resistant and rust-free.

Four built-in expanding transverse dog leg clamps permit installation with or without pre-wire construction brackets in drywall or material with thickness of 0" to 13/16".

Electrical connection, up to 12 gauge wire, is made by gold plated constant tension spring loaded terminals.

With our limited Lifetime warranty you are assured years of superior trouble free operation.

| | |
|-------------|--|
| Part Number | 92025 |
| Manual URL | www.currentaudio.com |
| Accessories | Volume Control ZL45R Part# 92034 SpeKap Part # 92069 |



SPECIFICATIONS

| | |
|--|--|
| Driver | 6.5" MetaPlex Composite Cone |
| Tweeter | 1" (25mm) Silk Ferrofluid Cooled Dome |
| Crossover | Gold press terminals |
| Grill specification | Perforated Aluminum with Scrim Cloth |
| Frequency Response | 42Hz - 20kHz |
| Impedance (nominal) | 8 ohms |
| Power Handling | 5 - 100 Watts |
| SPL | 90 dB 1W/1m |
| Length x Width x Depth | 12 1/4" (311mm) x 8 3/16" (208mm) x 3 1/16" (78mm) |
| Retrofit Cutout Diameter | 10 11/16" (272mm) x 6 5/8" (168mm) |
| Standard Pair Pack Dimensions (weight) | 9 3/4" x 13 3/4" x 11" (10 lbs) |
| Master Pack Dimensions 2 pair (weight) | 19 1/2" x 13 3/4" x 11" (20 lbs) |

