

WS651

6.5" 2-Way, In-Wall, Full Range Loudspeaker

The easy to install WS651 is a full-range In-Wall loudspeaker that incorporates an Injection Molded Carbon Fiber woofer with a butyl rubber surround and an aluminum dome Ferrofluid cooled tweeter. This tweeter allows for deeper penetration into the room and concentrated sound to the sweet spot. This revolutionary combination provides superior and more natural sound for both foreground and background applications.

In addition the WS651 incorporates a 3 position equalization switch, one each for bass and treble to fine tune the acoustics and allow for various room surfaces.

For efficiency and consistency the WS651 is timbre matched to the FIT651, and CS651 series of speakers.

The speaker color is white, and is a close match to Frazee White Shadow 181. It can be painted to match any décor. The speaker enclosure is a durable UV-resistant material that allows for both indoor and outdoor installations. The perforated powder-coated aluminum alloy grill is long lasting, corrosion resistant and rust-free.

Four built-in expanding transverse dog leg clamps permit installation with or without pre-wire construction brackets in drywall or material with thickness of 0" to 13/16".

Electrical connection, up to 12 gauge wire, is made by gold plated constant tension spring loaded terminals.

With our limited Lifetime warranty you are assured years of superior trouble free operation.

Part Number	92024
Manual URL	www.currentaudio.com
Accessories	Volume Control ZL45R Part# 92034 SpeKap Part # 92069



SPECIFICATIONS

Driver	6.5" Injection Molded Carbon Fiber Cone with Butyl Rubber Surround
Tweeter	1" (25mm) Aluminum Dome
Crossover	3 position EQ switches for Driver and Tweeter adjustments, gold press terminals
Grill specification	Perforated Aluminum with Scrim Cloth
Frequency Response	40Hz - 20kHz
Impedance (nominal)	8, 6 or 4 ohms dependent upon driver EQ switch setting
Power Handling	5 - 125 Watts
SPL	90 dB 1W/1m
Length x Width x Depth	12 1/4" (311mm) x 8 3/16" (208mm) x 3 1/16" (78mm)
Retrofit Cutout Diameter	10 11/16" (272mm) x 6 5/8" (168mm)
Standard Pair Pack Dimensions (weight)	9 3/4" x 13 3/4" x 11" (10 lbs)
Master Pack Dimensions 2 pair (weight)	19 1/2" x 13 3/4" x 11" (20 lbs)

