

CS501FL

5.25" 2-Way, In-Ceiling, Coaxial, Infinite Baffle Loudspeaker w/FastLoc Grille

The easy to install CS501FL is a full-range ceiling loudspeaker that incorporates an Injection Molded Graphite woofer with a butyl rubber surround and Ferrofluid cooled titanium coated polycarbonate tweeter. The tweeter allows for deeper penetration into the room and concentrated sound to the sweet spot.

The FastLoc™ grille patent no. 8,422,722, is a feature found only at Current Audio. Our design has allowed for the smallest exposed plastic bezel in the industry, truly making it disappear into the mounting surface. The FastLoc grille's unique patent pending mechanism allows for a quick installation and removal of the grille while securely fastening it in place to all types of mounting surfaces. Due to the unique design the grille will conform to uneven surfaces including popcorn, heavy textured and uneven ceilings. While our competitors have chosen to utilize magnets in their designs thus requiring the use of a steel grille that will rust our design allows us to use corrosion and rust resistant aluminum.

This revolutionary combination provides superior and more natural sound for both foreground and background applications. The Infinite Baffle design makes it the ideal choice for typical applications in open beam attic or enclosed ceilings.

The speaker color is white, and is a close match to Frazee White Shadow 181. It can be painted to match any décor. The speaker enclosure is a durable UV-resistant material that allows for both indoor and outdoor installations. The perforated powder-coated aluminum alloy grill is long-lasting, corrosion resistant and rust-free.

Four built-in expanding transverse dog leg clamps permit installation with or without pre-wire construction brackets in drywall or material with thickness of 7/32" to 1 3/16".

Electrical connection, up to 12-gauge wire, is made by gold plated constant tension spring-loaded terminals.



SPECIFICATIONS

Driver	5.25" Injection Molded Graphite Cone with Butyl Rubber Surround
Tweeter	.75" (19mm) Titanium Coated Polycarbonate Ferrofluid Cooled Dome
Crossover	Gold press terminals
Grill specification	Perforated Aluminum with Scrim Cloth
Frequency Response	55Hz - 19kHz
Impedance (nominal)	8 ohms
Power Handling	5 - 45 Watts
SPL	89 dB 1W/1m
Diameter x Depth	8" (203mm) x 3 1/4" (83mm)
Retrofit Cutout Diameter	6 1/2" (165mm)
Standard Pair Pack Dimensions (weight)	11 1/4" x 9" x 9 1/2" (6 lbs)
Master Pack Dimensions 2 pair (weight)	18 1/2" x 12" x 10 1/4" (15 lbs)



Part Number	92403
Manual URL	www.currentaudio.com
Accessories	Volume Control ZL75R Part# 92034 SpeKap Part # 92069



CURRENTAUDIO®

©2017 Current Audio • 8141 Center St, La Mesa, CA 91942 • Sales 866-927-7181
All product specifications are subject to change without notice.

Rev. SS-CS501FL 11/10